

The Brand of Progress

DVH 655 E



Advantages

- Resiliently mounted guide bar with multiple vibration absorbers ensures a non-fatiguing work place for the operator.
- Low maintenance and easily accessible Diesel engine mounted at the front of the machine.
- ▶ Tank mounted at the rear of the roller as additional sound protection for the operator.
- Engine with an electric starter.
- Hinged guide bar can be swung up and locked in the upright position for easy transport.

- ► The slim side of the roller is free from protruding components for compacting right up to lateral obstructions.
- ► High ground clearance.
- Central lifting lug for safe and easy hoisting.
- Four lashing points for safe truck transport.
- Cooler fan for the engine compartment and hydraulics for increased protection against overheating.
- Water tank and tubing made of non-corroding and durable PVC.

Hydrostatic duplex rolles




The Brand of Progress

Technical features

| Туре | | DVH 655 E |
|--|-------------------|------------------------|
| Service weight as per CECE | kg (lbs) | 732 (1615) |
| Drum width | mm (in.) | 650 (25.6) |
| Drum diameter | mm (in.) | 400 (16) |
| Centrifugal force | kN (lbs) | 21 (4750) |
| Frequency | Hz (r.p.m) | 62 (3720) |
| Engine manufacturer | | Lombardini / 15 LD 420 |
| Engine type | | Diesel |
| Engine output, max. | kW/HP | 7,3 (10,0) |
| Engine power output at operation speed | kW (HP) at r.p.m. | 6,3 (8,6) at 3300 |
| Working speed | m/min (ft/min) | 0-75 (0-250) |
| Water tank capacity | L (gal) | 60 (15.9) |

We reserve the right to amend the specifications without prior notice.



Dimensions in mm.